



問題集

http://www.ktest.jp 1年で無料進級することに提供する Exam : 300-715

Title: Implementing and

Configuring Cisco Identity

Services Engine (SISE)

Version: DEMO

- 1. What are two components of the posture requirement when configuring Cisco ISE posture? (Choose two)
- A. updates
- B. remediation actions
- C. Client Provisioning portal
- D. conditions
- E. access policy

Answer: B, D

- 2. What is a method for transporting security group tags throughout the network?
- A. by enabling 802.1AE on every network device
- B. by the Security Group Tag Exchange Protocol
- C. by embedding the security group tag in the IP header
- D. by embedding the security group tag in the 802.1Q header

Answer: B

- 3. Which two ports must be open between Cisco ISE and the client when you configure posture on Cisco ISE? (Choose two).
- A. TCP 8443
- B. TCP 8906
- C. TCP 443
- **D. TCP 80**
- E. TCP 8905

Answer: A, E

- 4. Which profiling probe collects the user-agent string?
- A. DHCP
- B. AD
- C. HTTP
- D. NMAP

Answer: C

- 5. Which supplicant(s) and server(s) are capable of supporting EAP-CHAINING?
- A. Cisco AnyConnect NAM and Cisco Identity Service Engine
- B. Cisco AnyConnect NAM and Cisco Access Control Server
- C. Cisco Secure Services Client and Cisco Access Control Server
- D. Windows Native Supplicant and Cisco Identity Service Engine

Answer: A