# *KTest*

更に上のクオリティ　更に上のサービス

# 問題集

# Exam  :     303-300

# Title   :     LPIC-3 Security

# Version  :     DEMO

1.What option of mount.cifs specifies the user that appears as the local owner of the files of a mounted CIFS share when the server does not provide ownership information?
(Specify ONLY the option name without any values or parameters.)
Solution: uid=arg
Determine whether the given solution is correct?
A. Correct
B. Incorrect
Answer: A

2.Which of the following practices are important for the security of private keys?
(Choose TWO correct answers.)
A.Private keys should be created on the systems where they will be used and should never leave them.
B.Private keys should be uploaded to public key servers.
C.Private keys should be included in X509 certificates.
D.Private keys should have a sufficient length for the algorithm used for key generation.
E.Private keys should always be stored as plain text files without any encryption.
Answer: C D

3.What is the purpose of NSEC3 in DNSSEC?
A.To provide information about DNSSEC key signing keys
B.To prevent zone enumeration
C.To authenticate a DNS server
D.To sign a DNS zone
Answer: B

4.Which command is used to run a new shell for a user changing the SELinux context?
(Specify ONLY the command without any path or parameters.)
Solution: newrole
Determine whether the given solution is correct?
A. Correct
B. Incorrect
Answer: A

5.Which file is used to configure AIDE?
A./etc/rkhunter.conf
B./etc/audit/auditd.conf
C./etc/aide/aide.conf
D./etc/maldet.conf
Answer:C