

KTest

更に上のクオリティ 更に上のサービス



問題集

<http://www.ktest.jp>

1年で無料進級することに提供する

Exam : **642-591**

Title : Implementing Cisco NAC
Appliance

Version : DEMO

1.The NAS is configured to autogenerate an IP address pool of 30 subnets with a netmask of /30, beginning at address 192.168.10.0. Which IP address is leased to the end-user host on the second subnet?

- A.192.168.10.4
- B.192.168.10.5
- C.192.168.10.6
- D.192.168.10.7

Correct:C

2.Which default administrator group has delete permissions?

- A.admin
- B.help-desk
- C.add-edit
- D.full-control

Correct:D

3.What is the result when the condition statement in a Cisco NAA check for required software evaluates to false on a client machine?

- A.The required software is automatically downloaded to the user device.
- B.The required software is made available after the user is quarantined.
- C.The user is put in the unauthenticated role and the software is considered missing.
- D.The user is placed in the temporary role and the software is made available.

Correct:B

4.Which three components comprise a Cisco NAC Appliance solution? (Choose three.)

- A.a NAC-enabled Cisco router
- B.a Linux server for in-band or out-of-band network admission control
- C.a Linux server for centralized management of network admission servers
- D.a Cisco router to provide VPN services
- E.a read-only client operating on an endpoint device
- F.a NAC-enabled Cisco switch

Correct:B C E

5.Drop

Click and drag the default username from the left to the correct description on the right. (Choose three.)

- normal role
- blocked role
- authenticated role
- quarantine role
- remediation role
- temporary role

- assigned to this role after vulnerabilities are found in a network scan
- assigned to this role when Cisco NAA end-user policy requirements are not met
- assigned to this role after a successful login

Correct:

Green choice1---->Yellow Choice3

Green choice6---->Yellow Choice2

Green choice4---->Yellow Choice1

6.Drop

Click and drag each feature of a Cisco NAC Appliance solution from the left to its correct benefit on the right.

- vulnerability assessment
- authentication integration
- traffic-filtering policies
- centralized management
- remediation and repair
- adaptable levels of enforcement

- has a web-based management console that can manage several servers
- provides access to OS patches and updates, virus and spam filters, and endpoint security
- scans for specific endpoint devices and roles, and adjusts for required remediation
- supports Kerberos, LDAP, RADIUS, Active Directory, S/Ident
- supports role-based policies
- supports scanning of network-based operating systems and non-PC networked devices

Correct:

Green choice1---->Yellow Choice6

Green choice2---->Yellow Choice4

Green choice3---->Yellow Choice5

Green choice4---->Yellow Choice1

Green choice5---->Yellow Choice2

Green choice6---->Yellow Choice3

7. When configuring the Cisco NAM to implement Cisco NAA requirement checking on client machines, what is the next step after configuring checks and rules?

- A. retrieve updates
- B. require the use of the Cisco NAA
- C. configure session timeout and traffic policies
- D. map rules to requirement
- E. configure requirements

Correct: E

8. Refer to the exhibit. When logging in to a Cisco NAC Appliance solution, an end user is prompted for a username, password, and provider. What should be entered in the Provider drop-down field shown in the exhibit?



- A. the authenticating NAS
- B. the authorizing NAM
- C. the name of the ISP
- D. the external authenticating server

Correct: D

9. What are the two types of traffic policies that apply to user roles? (Choose two.)

- A. IP-based
- B. peer-based
- C. host-based
- D. manager-based
- E. server-based
- F. VLAN-based

Correct: A C

10. After you implement a network scan and view the report, you notice that a plug-in did not access any of its dependent plug-ins. What did you forget to do?

- A. enable the Dependent Plug-in check box on the General Tab form
- B. configure dependent plug-in support when you mapped the Nessus scan check to the Nessus plug-in rule
- C. install dependent plug-ins when you updated the Cisco NAC Appliance plug-in library
- D. load the dependent plug-ins for that plug-in in the Plug-in Updates form

Correct: D

