

# KTest

更に上のクオリティ 更に上のサービス



## 問題集

<http://www.ktest.jp>

1年で無料進級することに提供する

**Exam** : **CS0-003**

**Title** : **CompTIA Cybersecurity  
Analyst (CySA+) Exam**

**Version** : **DEMO**

1.A recent zero-day vulnerability is being actively exploited, requires no user interaction or privilege escalation, and has a significant impact to confidentiality and integrity but not to availability.

Which of the following CVE metrics would be most accurate for this zero-day threat?

- A. CVSS: 31/AV: N/AC: L/PR: N/UI: N/S: U/C: H/I: K/A: L
- B. CVSS:31/AV:K/AC:L/PR:H/UI:R/S:C/C:H/I:H/A:L
- C. CVSS:31/AV:N/AC:L/PR:N/UI:H/S:U/C:L/I:N/A:H
- D. CVSS:31/AV:L/AC:L/PR:R/UI:R/S:U/C:H/I:L/A:H

**Answer: A**

**Explanation:**

This answer matches the description of the zero-day threat. The attack vector is network (AV:N), the attack complexity is low (AC:L), no privileges are required (PR:N), no user interaction is required (UI:N), the scope is unchanged (S:U), the confidentiality and integrity impacts are high (C:H/I:H), and the availability impact is low (A:L). Official.

Reference: <https://nvd.nist.gov/vuln-metrics/cvss>

2.Which of the following tools would work best to prevent the exposure of PII outside of an organization?

- A. PAM
- B. IDS
- C. PKI
- D. DLP

**Answer: D**

**Explanation:**

Data loss prevention (DLP) is a tool that can prevent the exposure of PII outside of an organization by monitoring, detecting, and blocking sensitive data in motion, in use, or at rest.

3.An organization conducted a web application vulnerability assessment against the corporate website, and the following output was observed:



Which of the following tuning recommendations should the security analyst share?

- A. Set an HttpOnly flag to force communication by HTTPS
- B. Block requests without an X-Frame-Options header
- C. Configure an Access-Control-Allow-Origin header to authorized domains
- D. Disable the cross-origin resource sharing header

**Answer:** B

**Explanation:**

The output shows that the web application is vulnerable to clickjacking attacks, which allow an attacker to overlay a hidden frame on top of a legitimate page and trick users into clicking on malicious links. Blocking requests without an X-Frame-Options header can prevent this attack by instructing the browser to not display the page within a frame.

4. Which of the following items should be included in a vulnerability scan report? (Choose two.)

- A. Lessons learned
- B. Service-level agreement
- C. Playbook
- D. Affected hosts
- E. Risk score
- F. Education plan

**Answer:** D, E

**Explanation:**

A vulnerability scan report should include information about the affected hosts, such as their IP addresses, hostnames, operating systems, and services. It should also include a risk score for each vulnerability, which indicates the severity and potential impact of the vulnerability on the host and the

organization. Official

Reference: <https://www.first.org/cvss/>

5. The Chief Executive Officer of an organization recently heard that exploitation of new attacks in the industry was happening approximately 45 days after a patch was released.

Which of the following would best protect this organization?

- A. A mean time to remediate of 30 days
- B. A mean time to detect of 45 days
- C. A mean time to respond of 15 days
- D. Third-party application testing

**Answer:** C

**Explanation:**

A mean time to remediate (MTTR) is a metric that measures how long it takes to fix a vulnerability after it is discovered. A MTTR of 30 days would best protect the organization from the new attacks that are exploited 45 days after a patch is released, as it would ensure that the vulnerabilities are fixed before they are exploited