

# ***KTest***

更に上のクオリティ 更に上のサービス



## 問題集

<http://www.ktest.jp>

1年で無料進級することに提供する

**Exam** : **HP0-436**

**Title** : OpenVMS v7 Network  
Administration

**Version** : DEMO

**1.What do you do to preserve site-specific parameter settings and commands for a specific TCPIP service?**

- A.Edit SYS\$SYSTARTUP:TCPIP\$SYSTARTUP.COM
- B.Edit SYS\$SYSTEM:TCPIP\$SYSTARTUP.COM
- C.Create files of the form SYS\$SYSTEM:TCPIP\$service\_SYSTARTUP.COM
- D.Create files of the form SYS\$STARTUP:TCPIP\$service\_SYSTARTUP.COM

**Correct:D**

**2.What driver does SCA use to run cluster traffic on NICs?**

- A.SYS\$NIDRIVER.EXE
- B.SYS\$PEDRIVER.EXE
- C.SYS\$EWDRIVER.EXE
- D.SYS\$PADRIVER.EXE

**Correct:B**

**3.Which command is a prerequisite to using sysconfig -q socket?**

- A.SYSCONFIG ENABLE
- B.@TCPIP\$DEFINE\_COMMANDS
- C.SET PROCESS/PRIVILEGE = ALL
- D.@TCPIP\$DEFINE\_SYSCONFIG

**Correct:B**

**4.After replacing a DECserver, you cannot connect to it using SET HOST/MOP. Using NCL, what needs to be modified?**

- A.MOP client address
- B.MOP circuit address
- C.MOP listener address
- D.MOP client node id

**Correct:A**

**5.An OpenVMS system acts as a primary BIND server. Which options statement in the BIND configuration file enables a secondary BIND server to receive a copy of the same database?**

- A.transfer-out
- B.query-source
- C.allow-transfer
- D.allow-update

**Correct:C**

**6.How do you determine the total number of incoming TCP requests?**

- A.TCPIP TRACE
- B.netstat -m
- C.TCPIP SHOW PROTOCOL TCP
- D.TCPIP SHOW TCP

**Correct:C**

**7.How do you determine which NIC has cluster traffic running on it?**

- A.SHOW CLUSTER /CONTINUOUS
- B.NCL> SHOW PROTOCOLS
- C.SDA> SHOW LAN
- D.SHOW CLUSTER /PORT

**Correct:C**

**8.Which commands can be used to monitor "unavailable station buffers"? Select TWO.**

- A.SDA> SHOW DEV EWA0: /COUNTER
- B.LANCP> SHOW DEV EWA0: /COUNTER
- C.NCL> SHOW ROUTING CIRCUIT EWA-0 COUNTER
- D.LANCP> SHOW LAN /COUNTER
- E.SDA> SHOW LAN /COUNTER

**Correct:B E**

**9.We have a two-node cluster connected only by a Fast Ethernet switched LAN. Both nodes have locally attached disks. We need to backup the data on both nodes A and B with a tape library on node A. We do not have enough network bandwidth to backup up the data in the time allowed. Which approach will increase bandwidth and decrease backup time?**

- A.Install a GIGAswitch/FDDI between nodes A and B.
- B.Add a Gigabit adapter to each system with a crossover cable.
- C.Install another tape drive in the tape library on node A.
- D.Replace the 10/100 adapter on node A with a Gigabit adapter.

**Correct:B**

**10.Where would you look to determine what LPR printers are enabled on your system?**

- A.SYS\$SPECIFIC:[TCPIP\$LPD]:TCPIP\$PRINTCAP.DAT
- B.SYS\$SYSDEVICE:[TCPIP\$LPD]TCPIP\$PRINTCAP.DAT
- C.SYS\$SYSTEM:QMAN\$MASTER.DAT
- D.The output of TCPIP SHOW SERVICE LPR /FULL

**Correct:A**

**11.What returns the current number of active network connections on a DECnet-Plus system?**

- A.NCL> SHOW NSP ALL STATUS NCL> SHOW OSI TRANSPORT ALL STATUS
- B.NCL>SNAPSHOT NODE 0 ALL COUNTERS NCL> SHOW EXECUTIVE CONNECTIONS
- C.MONITOR DECNET/CONNECTIONS
- D.SDA> SHOW CONNECTIONS

**Correct:A**

**12.What purpose does the SNAPSHOT command in NCL serve?**

- A.saves counters to a file
- B.monitors DECnet health
- C.saves and displays counters' values
- D.displays and zeroes old counters

**Correct:C**

**13.Which indication from MONITOR SYSTEM shows a need to upgrade from Fast Ethernet to Gigabit Ethernet?**

- A.compute queue with several processes
- B.high hard pagefault rate
- C.very few elements on freelist
- D.high buffered I/O rate

**Correct:D**

**14.Which system resource is depleted, as you increase the number of IP users?**

- A.PQL\_MFILLIM

- B.PQL\_MPGFLQUOTA
- C.GBLSECTIONS
- D.NPAGEDYN

**Correct:D**

**15.Which characteristics must be adjusted, when increasing the number of NSP "Maximum Transport Connections"? Select TWO.**

- A.Maximum Window
- B.Maximum Remote NSAPS
- C.Maximum Receive Buffers
- D.Maximum RJOBLIM
- E.Maximum Network Connections

**Correct:B C**

**16.Which command connects to a terminal server console with DECnet-Plus?**

- A.SET HOST/MOP
- B.SET HOST/LAT
- C.NCP> CONNECT NODE
- D.NCP> CONNECT VIA

**Correct:A**

**17.What SMTP setting allows sending mail outside of your zone?**

- A.General gateway
- B.Zone
- C.Alternate gateway
- D.Substitute domain

**Correct:C**

**18.Which OpenVMS networking command generated the following output? Proto Recv-Q Send-Q Local Address Foreign Address (state) tcp 0 0 sable.telnet tsc.2097 ESTABLISHED tcp 0 0 sable.telnet tsc.2089 ESTABLISHED tcp 0 0 sable.1612 sable.1035 ESTABLISHED tcp 0 0 sable.1035 sable.1612 ESTABLISHED tcp 0 0 sable.nvcold sable.1034 ESTABLISHED tcp 0 0 sable.telnet joe.osn.cxo.d.2889**

- A.NETSTAT
- B.NTPTRACE
- C.IFCONFIG
- D.TCPTRACE

**Correct:A**

**19.What is a similarity between TCPIP Proxy and DECnet Proxy?**

- A.use the same Proxy Database
- B.use AUTHORIZE to manage the database
- C.allow remote users to access files
- D.allow remote users anonymous access

**Correct:C**

**20.Which utility configures full/half duplex on EWAO?**

- A.MOP
- B.TCPIP
- C.LANCP

D.NCL

**Correct:C**