KTest

高品質　より良いサービス



練習問題

https://www.ktest.jp

1年間無料アップデート

Exam : **HP0-662**

Title : NonStop Configuration and Planning

Version : DEMO

1. Assuming no I/O enclosures, how many electrical branch circuits are needed to provide power fault tolerance for a six-processor S7x000 system?

A. 2

B. 3

C. 4

D. 6

Answer: D

2. Which items would you expect to see on a network topology diagram? Select TWO.

A. tape devices

B. IP addresses

C. routers

D. disk mapping

E. cable specifications

Answer: BC

3. What allows a customer to track open problem cases through the Web?

A. Scout for NonStop servers

B. Express Notice

C. NonStop Technical Library (NTL)

D. Total Web Support (TWS)

Answer: D

4. Which prediction is NOT produced by TCM?

A. number of processors required

B. number of logical disk volumes

C. network response time

D. processor and disk utilization

Answer: C

5. Which tool simplifies the task of migrating a database from many small disks to a smaller number of

large disks?

A. MEDIACOM

B. ASAP

C. SMF

D. MAPPER

Answer: C

6. DSM/SCM can be used to control customer software. Which program is used to prepare the software?

A. CNFGINFO

B. ZPHIRNM

C. INITENV

D. INITSTAT

Answer: A

7. To what type of adapter does a default configuration system console connect?

A. E4SA

B. MIOE

C. FESA

D. TRSA

Answer: B

8. Which process needs to be configured to ensure Expand connectivity between two systems?

A. $znet

B. $ncp

C. $expand

D. $zzatm

Answer: B

9. How many internal disk SCSI controllers are on a PMF CRU?

A. 0

B. 1

C. 2

D. 3

Answer: C

10. Which element is typically included in a separate document in response to a Request for Proposal (RFP)?

A. software details

B. timescales

C. cost breakdown

D. hardware details

Answer: C

11. Increasing the number of processors in a system _____.

A. provides fault tolerance for the system consoles

B. allows more disk units in group 1 of the system

C. requires a cold load of the system

D. allows more low-pin processes to run in the system

Answer: D

12. Which product can be used to project transaction growths into a resource upgrade timeline?

A. GPA

B. ASAP

C. NSX

D. TCM

Answer: D

13. What is the filename of the SCSI boot code for the G06.08 release?

A. I1000

B. IBOOT

C. I2000

D. ISCSI

Answer: B

14. Which utility is used for routine tape management operations?

A. TAPECOM

B. NSKCOM

C. MEDIACOM

D. TMFCOM

Answer: C

15. Which product requires a manual firmware update using TSM?

A. FESA

B. E4SA

C. SWAN

D. TRSA

Answer: C

16. Which tool has replaced Timbuktu for remote support?

A. Timbuk3

B. Remote Copy

C. Carbon Copy

D. PC Anywhere

Answer: C

17. What is a key difference between TSM low-level link and TSM service connection?

A. service connection communicates only with the MSP

B. service connection shows external devices

C. service connection allows firmware updates

D. service connection allows system discovery

Answer: B

18. Which Windows NT services are required when configuring dial-out on TSM? Select TWO.

A. RPC

B. RAS

C. SAP Agent

D. Network Monitor Agent

E. SNMP

Answer: BE

19. In which volume and subvolume do the hardware configuration files reside?

A. $system.system

B. $system.sysnn

C. $system.zsysconf

D. $dsmscm.system

Answer: C

20. How can the ServerNet connectivity to CPU 5 be displayed in SCF?

A. INFO SERVERNET 5

B. STATUS SERVERNET $ZSNET

C. INFO SERVERNET $ZSNET

D. STATUS SERVERNET 5

Answer: B