

# ***KTest***

更に上のクオリティ 更に上のサービス



## **問題集**

<http://www.ktest.jp>

1年で無料進級することに提供する

**Exam** : **HP0-771**

**Title** : Designing & Implementing  
HP Enterprise Backup  
Solutions

**Version** : DEMO

**1.The administrator is unable to verify who has an open session with Command View ESL. The administrator needs to access the library to update the firmware. Which two actions should the administrator take in order to upgrade the firmware? (Choose two).**

- A.Power cycle the library.
- B.Run the CLI via a serial cable.
- C.Run the CLI via telnet.
- D.Power cycle the backup server.

**Correct:B C**

**2.What two levels of library access does the advanced mode of Secure Manager allow? (Choose two.)**

- A.drive
- B.zone
- C.library
- D.backup

**Correct:A C**

**3.Which of the following steps should the administrator perform after installing Command View ESL? (Choose two).**

- A.Configure host access to the library.
- B.Configure SCSI IDs for each tape drive.
- C.Configure encryption settings for the library.
- D.Configure identification properties for each library.
- E.Configure compression settings for each tape drive.

**Correct:A D**

**4.A customer finds that backup jobs are unsuccessful. The backup software is able to detect the library and its tape drives. The customer stops all backup jobs and decides to update the firmware for the MSL6060 library using Library and Tape Tools but, Library and Tape Tools is unable to start the firmware upgrade. Which should be performed?**

- A.Download the latest patches for the backup software.
- B.Install Library and Tape Tools on a workstation instead.
- C.Verify that the Fibre Channel Interface Controller detects the library.
- D.Stop the backup application services or daemons on the backup server.

**Correct:D**

**5.A customer is using a MSL6060 library with four tape drives. The library is directly attached to a server via SCSI HBAs. The library currently has no cards in the cPCI slots. The customer wishes to share the tape library in a SAN environment. Which two hardware changes to the library will be needed, assuming that all other components in the SAN already exist? (Choose two.)**

- A.The customer should connect a Fibre cable from the existing Library Controller board into a Fibre Channel switch.
- B.The customer should remove the existing Library Controller board and replace it with a Fibre Channel Library Controller board.
- C.The customer should add a Network Storage Router M2402 to the SAN and connect the tape drives to the router.
- D.The customer should add two e1200-160 Interface Controllers to the cPCI slots and connect the tape drives to the Interface Controllers.

E.The customer should add one e2400-160 Interface Controller into a cPCI slot and connect the tape drives to the Interface Controller.

**Correct:C D**