

# KTest

更に上のクオリティ 更に上のサービス



## 問題集

<http://www.ktest.jp>

1年で無料進級することに提供する

**Exam** : **NS0-170**

**Title** : Network Appliance  
NetCache

**Version** : Demo

1. A complete listing of Network Appliance support centers is available at \_\_\_\_\_.

- A. www.netapp.com
- B. ftp.netapp.com
- C. now.netapp.com
- D. NetCache online help

Answer: C

2. The NetCache appliance may be used for all of the following EXCEPT \_\_\_\_\_.

- A. HTTP URL filtering
- B. SMTP proxy
- C. DNS caching
- D. NFS caching

Answer: B

3. Which TWO vendors?content filtering databases are supported on the NetCache?

- A. SurfControl
- B. WebWasher
- C. Secure Computing
- D. TrendMicro

Answer: BC

4. Which one of the following services is not a service supported by ICAP?

- A. Virus scanning of content received through HTTP.
- B. Virus scanning of email content
- C. URL filtering
- D. Active content stripping

Answer: B

5. Network Appliance field alerts \_\_\_\_\_ and \_\_\_\_\_.

- A. are available at "www.netapp.com"

B. may be received via email

C. are available at "now.netapp.com"

D. replace autosupport

Answer: BC

6. Network Appliance maintains a record of customer product information on the NOW site and this data is \_\_\_\_\_ .

A. available to anyone with NOW access

B. only available to authorized users

C. available only during business hours

D. only available to NetApp support staff

Answer: B

7. Which one of the following NetCache appliances has a maximum storage capacity of 504G Bytes?

A. C1200

B. C2100

C. C6200

D. All the above

Answer: B

8. Which TWO of the following statements are equivalent?

A. `set config.http.ports "8080" "8081"`

B. `set config.http.ports \ 8080`

`\`

C. `set config.http.ports // 8080 , 8081 \`

D. `set config.http.ports "8080 , 8081"`

Answer: AB

9. Which one of the following methods can be used to manage the NetCache appliance but cannot be used to access the Command Line Interface (CLI)?

- A. Console
- B. Telnet
- C. rsh
- D. HTTP

Answer: D

10. Which command would you use to see the available option choices for the show config.http.acl command?

- A. help
- B. show config.http.acl.?
- C. config.acl help
- D. help config.acl

Answer: B

11. When configuring a NetCache as a reverse proxy, you must \_\_\_\_\_ .

- A. write one or more acceleration rules
- B. reconfigure the client's browser
- C. write one or more ACLs
- D. have an acceleration license

Answer: A

12. When configured as an accelerator, the NetCache appliance is typically located close to the \_\_\_\_\_.

- A. client(s)
- B. gateway
- C. server
- D. resolver

Answer: C

13. The traceroute command is used to \_\_\_\_\_ .

- A. report interface activity in Kbps

- B. show the state of each interface
- C. print the route packets take to a network host
- D. display a list of active sockets for each protocol

Answer: C

14. You must \_\_\_\_ to reach the NetCache firmware prompt ("OK prompt").

- A. press Esc
- B. enter the halt command
- C. set the environment variable, floppy-boot?, to off
- D. enter the prompt command

Answer: B

15. The \_\_\_\_\_ command displays performance statistics, such as the current CPU usage, the amount of network I/O, and the amount of disk I/O.

- A. ifstat
- B. netstat
- C. stat
- D. sysstat

Answer: D

16. The NetCache appliance's clock can \_\_\_\_\_ and \_\_\_\_\_

- A. NOT be synchronized with a remote server
- B. be synchronized with NTP servers
- C. be synchronized with Windows domain controllers
- D. be synchronized with RDATE servers

Answer: BD

17. Which one is the CLI equivalent command for installing, committing, and rebooting a NetCache software image from the NetCache GUI assuming the server path is <http://10.1.1.1/nc-image.zip>?

- A. install <http://10.1.1.1/nc-image.zip>

B. `download -i -c -r http://10.1.1.1/nc-image.zip`

C. `install -dcr http://10.1.1.1/nc-image.zip`

D. `download -icr http://10.1.1.1/nc-image.zip`

Answer: C

18. Which one of the following access methods will maintain boot messages across reboots?

A. SSH

B. RSH

C. Telnet D. Console

Answer: D

19. The backup/restore options in the Maintenance section of the Appliance Manager are used to backup and restore \_\_\_\_\_ .

A. log files only

B. configuration files only

C. log files and configuration files

D. specified cached data

Answer: B

20. The console password can only be changed via \_\_\_\_\_ .

A. floppy disk

B. the console

C. rsh

D. the Appliance Manager

Answer: B